



VELATURA ACRILICA

Decorative Line

Description

This painting is excellent for obtaining shaded, veiled and ancient effects. It is very resistant to atmospheric agents, water, it preserves a good wall breathability and it is elastic. It has a glazed and velvet effect and can be applied on new, old and already painted plasters.

Thecnical data

- Composition: acrylic resins in water solution and high quality charges
- Physical status: semifluid paste
- Specific weight: 1.400 kg/l
- Flashpoint: unflammable
- Average viscosity: Ford n. 4, 20" a +20 °C
- Drying time: 1 hour to the touch, 6hours deeply
- Coating time: 2 hours minimum, according to the support absorption and outside temperature
- Result: 6/8 m2/liter, according to the effect desired
- Dry aspect: glazed and velvety
- Alkali resistance: good
- Tint: neutral
- Packages: 14, 5 and 2.5 litersPreservation: avoid freeze

Characteristics

Features and technical data Composition: acrylic resins in water solution and high quality charges Physical status: semifluid paste Specific weight: 1.400 kg/l Flashpoint: unflammable Average viscosity: Ford n. 4, 20? a +20 ?C Drying time: 1 hour to the touch, 6hours deeply Coating time: 2 hours minimum, according to the support absorption and outside temperature Result: 6/8 m2/liter, according to the effect desired Dry aspect: glazed and velvety Alkali resistance: good Tint: neutral Packages: 14, 5 and 2.5 liters Preservation: avoid freeze

Application

Apply with brush, roll, sponge. Dilution in 10% warter. Universal coloring or Colorification Veneziano's coloring can be added.

THE REPORTED DATA REFER TO LABORATORY TESTS: DURING PRACTICAL APPLICATIONS IN BUILDING SITES THESE CAN BE SLIGHTLY MODIFIED ACCORDING TO THE CONDITIONS OF ANY INSTALLATION. THE PERSON WHO WORKS WITH THE PRODUCT MUST VERIFY THE EXPECTED SUITABILITY OF USE OF THE PRODUCT, TAKING UPON HIMSELF.

THE COMPANY COLORIFICIO VENEZIANO S.R.L. MAY CARRY OUT TECHNICAL ALTERATIONS ON PRODUCTS WITHOUT NOTICE.