



VELATURA FREEZE

Decorative Line

Characteristics

Features Composition: acrylic resins in water solution and high quality charges Physical status: semifluid paste Specific weight: 1.400 kg/l Flashpoint: unflammable Average viscosity: Ford n. 4, 20? a +20 ?C Drying time: 1 hour to the touch, 6 hours deeply Coating time: 2 hours minimum, according to the support absorption and outside temperature Result: 6/8 m2/liter, according to the effect desired Dry aspect: glazed and velvety Alkali resistance: good Packages: 14, 5, 2.5 and 1.0 liters Preservation: avoid freeze

Other

Directions Apply with brush, roll, sponge. Dilution in 10% water. Universal coloring or Colorificio Veneziano?s coloring can be added.

THE REPORTED DATA REFER TO LABORATORY TESTS: DURING PRACTICAL APPLICATIONS IN BUILDING SITES THESE CAN BE SLIGHTLY MODIFIED ACCORDING TO THE CONDITIONS OF ANY INSTALLATION. THE PERSON WHO WORKS WITH THE PRODUCT MUST VERIFY THE EXPECTED SUITABILITY OF USE OF THE PRODUCT, TAKING UPON HIMSELF.

THE COMPANY COLORIFICIO VENEZIANO S.R.L. MAY CARRY OUT TECHNICAL ALTERATIONS ON PRODUCTS WITHOUT NOTICE.