



COLORIFICIO VENEZIANO

the Art of Paint

EL RAME

Decorative Line

Characteristics

Technical Information Appearance of the product: El Rame: Pasta Attivatore: Liquid

Dilution: El Rame: 5% -10% with water Attivatore: Ready to use

Application El Rame: brush or roller foam roller, Attivatore: brush, sponge or spray

Yield El Rame: 4-9 sqm / kg Attivatore: 8-14 m / lt

(Nb yields vary depending on the media and on the desired effect)

Other

Applications With suitable modifications in the application cycle, you can apply on EL RAME: ? Old paints or synthetic minerals ? Old gypsum plaster or lime ? Building plaster ? New plasters premixed finish civil ? Surfaces in plasterboard It is not advisable to apply this type of finish over fresh mineral surfaces, as it may jeopardize the process of oxidation of the liquid activator. Do not apply when moisture is present.

Preparing th Surface Clean the surface in the presence of poor or other impurities. In case of presence of mold or algae pretreat with suitable liquid algaecide, called DETERGENTE ANTIMUFFA, remove any loose stages of separation. Once the surface will be perfectly clean, continue with the application of an adhesion FONDO RUVIDO, in order to have a more homogenous surface without diversity of absorption,

Product Application When the surface will be completely dry, you can continue with the application of EL RAME and later, to complete drying, apply a coat of EL RAME ATTIVATORE to perfect drying apply a second coat in the necessary amount to achieve the desired effect, more activator is applied, the more intense will be the effect of oxidation.

Protection of External Surfaces FINISH FLOOR, MATT or GLOSS

Colors Not tinted

Packing EL RAME: 1kg, 5kg, 15kg EL RAME ATTIVATORE: 1 lt

Warnings It is advisable to complete each work with materials from the same batch production The material can be applied and stored at temperatures between + 5 ° and + 35 ° If stored in the original container has a term of one year. At the end of the application properly clean the tools with water.

THE REPORTED DATA REFER TO LABORATORY TESTS: DURING PRACTICAL APPLICATIONS IN BUILDING SITES THESE CAN BE SLIGHTLY MODIFIED ACCORDING TO THE CONDITIONS OF ANY INSTALLATION. THE PERSON WHO WORKS WITH THE PRODUCT MUST VERIFY THE EXPECTED SUITABILITY OF USE OF THE PRODUCT, TAKING UPON HIMSELF.

THE COMPANY COLORIFICIO VENEZIANO S.R.L. MAY CARRY OUT TECHNICAL ALTERATIONS ON PRODUCTS WITHOUT NOTICE.