



COLORIFICIO VENEZIANO

the Art
of
Paint

VELATURA LIDO

Decorative Line

Technical data

- Specific weight: 1.00 kg/l \pm 5%
- Yield: 16-17 m²/l depending on the desired effect and the substrate.
- Dilution: it can be used pure or diluted with a maximum of 10% water, depending on the final result you want to obtain.

Base preparation

The surface to be painted must be dry, free from dust and dirt, free from any traces of oil, grease and other deposits. If the substrate appears to be floury, apply **ISOLANTE ALTA PENETRAZIONE** or alternatively **ISOEDIL-A**. To complete the preparation of the base, apply a coat of **FONDO PER VELATURA METALLICA** pigmented in chromatic agreement with the desired color. Apply the product until the base is completely covered.

Application

After having prepared the bottom, you can proceed with the application of **VELATURA LIDO**. Depending on the desired effect, there are different application techniques:

- CLOUDY EFFECT: application with stainless steel trowel.
- ANTIQUE EFFECT: brush or roller. **VELATURA LIDO** is used as a decorative paint for interiors.

Warnings

- Apply the material only on cured and dry surfaces.

- Avoid application in the coldest periods of the year.
- Apply at a temperature higher than +5 °C and lower than +35 °C.

Preservation

Protect from frost. The material, if stored in suitable rooms, in the original packaging, has a shelf life of one year.

Quality

VELATURA LIDO is subjected to careful and constant control in our laboratories. The raw materials used are rigorously selected and controlled.

THE REPORTED DATA REFER TO LABORATORY TESTS: DURING PRACTICAL APPLICATIONS IN BUILDING SITES THESE CAN BE SLIGHTLY MODIFIED ACCORDING TO THE CONDITIONS OF ANY INSTALLATION. THE PERSON WHO WORKS WITH THE PRODUCT MUST VERIFY THE EXPECTED SUITABILITY OF USE OF THE PRODUCT, TAKING UPON HIMSELF.

THE COMPANY COLORIFICIO VENEZIANO S.R.L. MAY CARRY OUT TECHNICAL ALTERATIONS ON PRODUCTS WITHOUT NOTICE.