



IDROCEM-A PLUS

Professional Line

Description

good penetration depth resistance to alkalis rapid development of water repellency provides good adhesion to paints water based and compatible with every environment

Other

Preparation of the support Surfaces such as stone material or bricks:

dust and clean the surfaces; in the presence of patina of dirt, superficial crusts, scales, etc? we recommend clean the substrate with hydro-cleaning Environmental and support conditions:

Support temperature: Min. +5 ?C / Max. +35 ?C Media humidity: <10% ? avoid applications in the presence of surface condensation Indications for the application Tools: brush, low pressure spray Dilution: the material is ready to use In spray applications use diameter nozzles 1.2-1.4 mm The product performs its water-repellent action after one day from application. Protect treated surfaces from rain for at least 24 hours after application. Indicative yield: variable according to the absorption of the substrate. Preliminary tests are recommended. After impregnation wait until the water has evaporated. Painting The product is available colorless.

Maximum storage temperature: +30 ?C

Minimum storage temperature: +5 ?C

Stability in original unopened containers and in suitable temperature conditions: 18 months.

Storage It does not fall within the scope of Legislative Decree 161/2006

Not inflammable. Keep out of reach of children. Do not dispose of waste into drains. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or the label. The product must be transported, used and stored according to the current health and safety regulations; after use, do not dispose of the containers in the environment, allow the residues to dry completely and treat them as special waste. For more information, consult the safety data sheet.

THE REPORTED DATA REFER TO LABORATORY TESTS: DURING PRACTICAL APPLICATIONS IN BUILDING SITES THESE CAN BE SLIGHTLY MODIFIED ACCORDING TO THE CONDITIONS OF ANY INSTALLATION. THE PERSON WHO WORKS WITH THE PRODUCT MUST VERIFY THE EXPECTED SUITABILITY OF USE OF THE PRODUCT, TAKING UPON HIMSELF.

THE COMPANY COLORIFICIO VENEZIANO S.R.L. MAY CARRY OUT TECHNICAL ALTERATIONS ON PRODUCTS WITHOUT NOTICE.