



COLORIFICIO VENEZIANO

the Art
of
Paint

VELATURA 1000

Decorative Line

Description

VELATURA 1000 is a special painting for obtaining veiled, shaded effects. It is highly resistant to atmospheric agents and water. It is elastic, preserves wall breathability enough. It has got a glazed and velvety effect and can be applied on new, old and plasters that have been painted.

Technical data

- Specific weight: 1.120 kg/l +/- 5%
- Result: 7-10 m²/l according to the desired effect
- Dilution: can be used pure or diluted with 10% water maximum, according to the final result.
- pH value: between pH 6.5 and pH 7.5
- Viscosity: (Brookfield rot. n. 4a 20 Rpm), 8,000 cps with +21 °C
- Water vapor permeability: Sd 0.25 m (Maximum permitted 2 m, DIN 52 615)
- Emission limit for organic compounds: A/I; VOC: 30 g/l (maximum)

Base preparation

The surface must be clean and dry. Remove any grease and oil spot. If the base is chalky, apply [Isolante Alta Penetrazione](#), while if it is smooth use **FONDO RUVIDO**.

To complete the base preparation apply one layer of **FONDO VELATURA METALLICA**, a special kind of stucco paste.

Application

After preparing the base, you can apply **VELATURA 1000**.

According to the desired effect, there are several application techniques:

- Grassello 600 effect: use a steel spatula
- Ancient effect: use a brush or a roll

VELATURA 1000 is used as decorative painting for indoor and outdoor use.

Color

VELATURA 1000 is a decorative coating formed of resins in water emulsion and special metal pigments. With this product you can make many different decorative finishing.

Warnings

- Apply the material only on dry and seasoned surfaces.
- Avoid the application during the coldest months.
- Apply with a temperature higher than +5 °C and lower than +35 °C.

Preservation

Avoid freeze. If stored inside the original package in proper environments, it lasts 1 year.

Quality

VELATURA 1000 is constantly and properly checked in our laboratories. The raw materials used are strictly selected and checked.

THE REPORTED DATA REFER TO LABORATORY TESTS: DURING PRACTICAL APPLICATIONS IN BUILDING SITES THESE CAN BE SLIGHTLY MODIFIED ACCORDING TO THE CONDITIONS OF ANY INSTALLATION. THE PERSON WHO WORKS WITH THE PRODUCT MUST VERIFY THE EXPECTED SUITABILITY OF USE OF THE PRODUCT, TAKING UPON HIMSELF.

THE COMPANY COLORIFICIO VENEZIANO S.R.L. MAY CARRY OUT TECHNICAL ALTERATIONS ON PRODUCTS WITHOUT NOTICE.