



COLORIFICIO VENEZIANO

the Art
of
Paint

GRAFFIATO

Acrylic Surface Coatings

Description

GRAFFIATO is a finishing coating formed of special acrylic binders highly water repellant, very fine colored quartz sands resistant to light and chemical additives to improve the manufacturing and adherence.

The raw materials used allow a good transpiration of the wall. The addition of algae inhibitor and anti-molds additives allow an excellent resistance to atmospheric agents and bacteria. It allows to obtain a finishing surface of rustic effect.

Technical data

- Specific weight: 1.850 kg/l
- Dilution: ready to use
- Granulometry: 2.0 mm

Base preparation

The finishing coating must be applied after at least 28 days from the bottom plaster application.

The surface needs to be completely clean. Grease, oil and wax spots must be removed.

Chalked or absorbing bases must be treated with an insulating base, our **ISOEDIL-A** slightly diluted at a ratio of 1:5 with water.

We suggest to dilute **ISOEDIL-A** with **LAVEDIL SQ** when the surface to be coated presents absorbance diversities (doors and windows frames, etc.) or if you want to extend the working time.

To apply **GRAFFIATO**, the base plaster must be well finished.

In case of applying the coating over surfaces that are very smooth, not spongy and scarcely absorbent we suggest to apply a layer of **FONDO RUVIDO** slightly diluted in 50% weight with water, instead of using the base **ISOEDIL-A**.

Application

Lay the material on the surface with a metallic spatula paying attention to distributing one even layer of material. Use a plastic spatula to make the finishing with circular movements.

Warnings

GRAFFIATO must be used at its original status without adding any other material.

- For every work, collect the needed material all of the same kind.
- Apply only over seasoned and dry plasters.
- Avoid the application on facades with full sun and too much wind.
- Avoid the application during the coldest and most humid months of the year; +5 °C is the lowest temperature for the laying-up and application of the material.
- After applying, the surfaces must be protected by rain for at least 48 hours.
- Avoid the application of the material over a facade in different times.

Other

Use

GRAFFIATO is used as protective and decorative coating for external and internal spaces over lime and cement bases.

Preservation

Avoid the preservation in very cold places.

Preserve at temperatures higher than +5 °C and lower than +30 °C. If stocked in proper places lasts 1 year.

Quality

GRAFFIATO is constantly and properly checked in our laboratories. The raw materials used are strictly selected and checked.

THE REPORTED DATA REFER TO LABORATORY TESTS: DURING PRACTICAL APPLICATIONS IN BUILDING SITES THESE CAN BE SLIGHTLY MODIFIED ACCORDING TO THE CONDITIONS OF ANY INSTALLATION. THE PERSON WHO WORKS WITH THE PRODUCT MUST VERIFY THE EXPECTED SUITABILITY OF USE OF THE PRODUCT, TAKING UPON HIMSELF.

THE COMPANY COLORIFICIO VENEZIANO S.R.L. MAY CARRY OUT TECHNICAL ALTERATIONS ON PRODUCTS WITHOUT NOTICE.

Colorificio Veneziano srl
Via dell'Artigianato 10/12, 30030 Robegano VE, ITALY
Tel +39 041.482.954 / +39 041.482.814